

小型開邊式粘合機 OP-450GS/450GSL/520GS/520GSL

MINI OPEN-SIDE FUSING PRESS MACHINE

用途：

- ★ 針對平織 / 針織裁片之黏合工作。

優點：

- ★ 體積小易于搬運。
- ★ 開邊式：適合較大裁片，連袖裁片等。
- ★ 出料方式采用可分離式螺旋式撥片，強化裁片撥離之能力，而且裁片不易起泡變形。
- ★ 本機裝有特殊構造之輸送皮帶，可以排除皮帶的偏離，并確保其使用壽命。

- ★ 迷你黏合機具有特制壓力輔助裝置，保證最大壓力強度至1kg/cm²。
- ★ 電子溫度調節器，及特制加熱設備，將溫度差異範圍減至最小程度。
- ★ 采用極完美且能保持熱度在一定程度的鐵氟龍傳動帶 (Teflon)，而其清潔布杆可隨時保持皮帶之清潔。
- ★ 強力散熱風扇，降低電子零件處於高溫時之損害。
- ★ OP-450GSL/OP-520GSL為下皮帶加長型。



OP-450NS+450T脚架
Stand Only

Application :

- ★ For the interlining and fabrics fusing.

Feature :

- ★ Compact type that can be moved easily to any places.
- ★ Side-open style: Fit for the bigger fabrics and various sizes.
- ★ Rotary Strip-off device

- ★ Rotary Strip-off device for strengthening the stripping off function and avoid transforming of the finished fabrics.
- ★ Equipped with the super linear guide belt to prevent the belt from warping, and extend the duration of the belt.
- ★ Equipped with the special-designed pressure mechanism to ensure the maximum pressure strength up to 1kg/cm².
- ★ Electronic thermostat and the special-made heating equipment minimize the temperature differences.
- ★ OP-450GSL, and OP-520GSL: L series is the longer bottom belt for more efficient work.
- ★ Use the excellent heatproof Teflon belt. This patented Teflon Belt is easy of maintenance and clean.
- ★ Powerful ventilate fan to lower the temperature of electronic components from damaging.

規格 Specification

型號Model	OP-450GS	OP-450GSL	OP-520GS	OP-520GSL	OP-450NS
電壓Power Supply	1P/220V				
馬達功率Motor Power(kw)	0.06				
電熱功率Heater(kw)	3.6		4.2		3.6
使用壓力 Use Pressure(Mpa)	0.05~0.1				
設定溫度Temperature(°C)	常溫~200				
黏合寬度Fusing Width(mm)	450		520		450
黏合時間Fusing Time(Sec)	10~34				
刮布器Type of Scraper	旋轉撥片Rotary Stripe-Off				
機器尺寸L×W×H Dimensions(mm)	1700×910×360	2000×910×360	1700×980×360	2000×980×360	1700×910×360
裝箱尺寸L×W×H Packing Volume(mm)	1110×950×520	1420×950×520	1110×1100×530	1420×1100×530	1110×950×520
淨重/毛重N.W / G.W(kg)	145/170		170/200		145/170