

CYLINDER-BED/UNISON FEED

GOLDEN WHEEL



CS-8B

Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Standard hook)(Elliptical movement of bottom feed, for normal stitching)

Model No. CS-8B	S.P.M. 2,500
Max. Stitch Length 5mm	Lift Of Presser Foot (Knee) 14mm
Needle System DP×17 #22 (#19~#23)	Needle Bar Stroke 34mm
Alternating Movement 3~6mm	

This machine is equipped with walking foot, needle feed and feed dog, all of which act completely in unison feed. Consequently, the upper or lower sewing material did not slip and also this machine can sew accurately and easily several sheets of heavy materials piled up together. Equipped with a safety clutch mechanism which protected the rotating hook & needle from damage when the thread was caught in the rotating hook.

- The diameter of cylinder-bed is 65mm, is ideally suited for stitching tubular and curved articles, such as shoes, bags, small articles, purses,.....etc..

CS-8B

LV-1

Model:
Single Needle, Unison Feed, Cylinder-Bed Sewing Machine.

Code Description:

- : Standard Hook, Elliptical Movement Of Bottom Feed. (For normal stitching) (The diameter of cylinder-bed is 65mm)
- N: Standard Hook, Elliptical Movement Of Bottom Feed. (For normal stitching) (The diameter of cylinder-bed is 65mm) (New type of needle plate)
- V: Standard Hook, Horizontal Movement Of Bottom Feed. (For binding stitching) (The diameter of cylinder-bed is 65mm)
- L: Large Hook, Elliptical Movement Of Bottom Feed. (For normal stitching) (The diameter of cylinder-bed is 77mm)
- LV: Large Hook, Horizontal Movement Of Bottom Feed. (For binding stitching) (The diameter of cylinder-bed is 77mm)
- L-1: Large Hook, Elliptical Movement Of Bottom Feed. (For normal stitching) (The diameter of cylinder-bed is 77mm) (Small outer-end)
- LV-1: Large Hook, Horizontal Movement Of Bottom Feed. (For binding stitching) (The diameter

SPECIFICATIONS:

Model No.	Max. Sewing Speed S.P.M.	Lifting Of Presser Foot (Hand/Knee) mm	Max. Stitch Length mm	Needle Bar Stroke mm	Hook System	Needle System	The Alternating Movement Of Presser Foot mm
CS-8B	2500	8.5/14	5	34	Standard Hook	DP×17#22 (#19~#23)	3~6
CS-8BN	2500	8.5/14	5	34	Standard Hook		3~6
CS-8BV	2500	8.5/14	5	34	Standard Hook		3~6
CS-8BL	2000	8.5/14	6.2	34	Large Hook		3~6
CS-8BL-1	2000	8.5/14	6.2	34	Large Hook		3~6
CS-8BLV	2000	8.5/14	6.2	34	Large Hook		3~6
CS-8BLV-1	2000	8.5/14	6.2	34	Large Hook		3~6

- CS-8BN-K:With edge trimming function(The other special features are as CS-8BN.

CS-8BV



Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Standard hook)(Horizontal movement of bottom feed, for binding stitching)

- Suitable for stitching (Taping or piping or binding) the heavy materials. (For example: bags, shoes, purses and other tubular goods).

CS-8BLV



Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Large hook)(Horizontal movement of bottom feed, for binding stitching)

- Suitable for stitching (Taping or piping or binding) the heavy materials. (For example: bags, shoes, purses and other tubular goods).
- Applied with large hook, could increase the sewing efficiency.

GOLDEN WHEEL