



CS-28BL

Double Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Large hook)

Model No. CS-28BL	S.P.M. 2,000
Max. Stitch Length 6.2mm	Lift Of Presser Foot (Hand/Knee) 8.5/14mm
Needle System DP×17 #22 (#19~#24)	Needle Bar Stroke 34mm
Alternating Movement 3~6mm	

This machine is equipped with walking foot, needle feed and feed dog, all of which act completely in unison feed. Applied with large hook ensured high sewing efficiency. Equipped with a safety clutch mechanism which protected the rotating hook & needle from damage.

- The diameter of cylinder-bed is 81mm, is ideally suited for stitching tubular and curved articles, such as shoes, bags, small articles, purses.....etc..
- Standard needle gauge: 6.4mm.



CS-441

Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (For extra-heavy materials)

Model No. CS-441	S.P.M. 800
Max. Stitch Length (Knee) 11mm	Lift Of Presser Foot (Knee) 20mm
Needle System DY×3#26 (#23~#28)	Needle Bar Stroke 56mm
Dia. of Cylinder-Bed 81mm	
Alternating Movement 4~8mm	

Powerful unison feed mechanism, the machine can sew accurately and easily several sheets of heavy materials piled up together. The sewing area is up to 420 mm, suitable for stitching the huge articles.

- The lift of presser foot is up to 20 mm, suitable for stitching the extra-heavy materials.
- Applied the semi-rotary large shuttle hook & bobbin, could reduce the frequency of changing the bobbin thread, and increase the sewing efficiency.
- Suitable for stitching all the extra-heavy materials, such as the handle of bags, gloves, safety belts, tents, seatings, shoes, bags.....etc..



CS-2050

Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (For extra-heavy materials)



Model No. CS-2050	S.P.M. 800
Max. Stitch Length 10mm	Lift Of Presser Foot (Knee) 20mm
Needle System DY×3 #25 (#21~#28)	Needle Bar Stroke 56mm
Alternating Movement 4~10mm	

Powerful unison feed mechanism, the machine can sew accurately and easily several sheets of heavy materials piled together. The lift of presser foot is up to 20 mm, suitable for stitching the extra-heavy materials. The sewing area is up to 404 mm, suitable for stitching the huge articles.

- Applied the semi-rotary large shuttle hook & bobbin, could reduce the frequency of changing the bobbin thread, and increase the sewing efficiency.
- Suitable for stitching all the extra-heavy materials, such as safety belts, tents, seatings, shoes, bags, golf bags.....etc..



CS-411N

Single Needle, Bottom Feed, Super-Long Cylinder-Bed Sewing Machine. (For heavy materials horizontal stitching)



Model No. CS-411N	S.P.M. 800
Max. Stitch Length 11mm	Lift Of Presser Foot (Knee) 20mm
Dia. of Cylinder-Bed: 85 mm	Needle Bar Stroke 56mm
Sewing Area 178×935 mm	Needle System DY×3#26 (#23~#28)

The sewing area is up to 935 mm, (cylinder-bed length: 935 mm), suitable for stitching the huge articles, long-sized articles, and the tubular goods.

- The machine can sew accurately and easily several sheets of heavy materials piled up together.
- The lift of presser foot is up to 20 mm, suitable for stitching the heavy materials.
- Applied the semi-rotary large shuttle hook & bobbin, could reduce the frequency of changing the bobbin thread, and increase the sewing efficiency.
- Usage: Suitable for horizontal stitching all the heavy materials, such as inner case of golf bags.....etc..



CS-461

Single Needle, Union Feed, Super-Long Cylinder-Bed Sewing Machine. (For extra-heavy materials)

Model No. CS-461	S.P.M. 650
Max. Stitch Length 11mm	Lift Of Presser Foot (Knee) 20mm
Dia. of Cylinder-Bed: 81mm	Needle Bar Stroke 56mm
Sewing Area 180×950mm	Needle System DY×3#26 (#23-#28)
Alternating Movement 4-8mm	

The sewing area is up to 950 mm (cylinder-bed length: 950 mm), suitable for stitching the huge articles, long-sized articles, and the tubular goods.

- Due to the powerful feed, the machine can sew accurately and easily several sheets of heavy materials piled up together.
- The lift of presser foot is up to 20 mm, suitable for stitching the extra-heavy materials.
- Applied the semi-rotary large shuttle hook & bobbin, could reduce the frequency of changing the bobbin thread, and increase the sewing efficiency.
- Usage: Suitable for stitching all the extra-heavy materials, such as golf bags, carrying bags,etc..
- CS-491:Single Needle,Top & Bottom Feed,Super-Long Cylinder-Bed Sewing Machine.(For extra-heavy materials)



CS-810

Single Needle, Postbed Sewing Machine.

Model No. CS-810	S.P.M. 2,400
Max. Stitch Length 5mm	Lift Of Presser Foot (Knee) 11mm
Needle System DP×5#16 (#14-#19)	Needle Bar Stroke 36mm


Changed the roller presser foot accessories into the flat presser foot accessories, could stitch the cap and wig.

- CS-810C(For wig), CS-810E(For cap)
- Easy guiding of work when sewing the closed shoe uppers, e.g. children's, because the postbed is arranged to the right of the needle.
- Excellent sewing effects and first class quality due to vertical axis of rotating hook and link type of thread take-up lever.
- Suitable for sports shoes, lady shoes, jackboots, bags, caps, wigs,etc..



CS-810D-BT

Direct Drive, Single Needle, Postbed Sewing Machine. (Automatic undertrimming & automatic backtacking)



Model No. CS-810D-BT	S.P.M. 2,400
Max. Stitch Length 5mm	Lift Of Presser Foot (Knee) 11mm
Needle System DP×5#16 (#14-#19)	Needle Bar Stroke 36mm

Applied with direct drive servo motor, energy saving. Applied with the new type of automatic undertrimming mechanism, the undertrimming result is more perfect, it could reduce the consumption of thread, and increase the sewing efficiency.

Applied with the automatic backtacking device: the backtacking only with gentle press on the backtacking switch, easy operation and could increase the sewing quality & efficiency.

- The other special features are as CS-810.
- F: Automatic presser foot lifting. (Optional). (AF: Pneumatic type, MF: Electric type.).



CS-820

Double Needle, Postbed Sewing Machine.



Model No. CS-820	S.P.M. 2,400
Max. Stitch Length 4mm	Lift Of Presser Foot (Knee) 11mm
Needle System DP×5#16 (#14-#19)	Needle Bar Stroke 36mm

Excellent sewing effects and first class quality due to vertical axis of rotating hook and link type of thread take-up lever.

- Lockstitch with bottom feed can promise a smooth sewing quality on either thin or thick materials.
- Standard needle gauge: 1.6mm or 2.0mm or 2.4mm.
- Suitable for sports shoes, lady shoes, jackboots, bags,etc..
- CS-820D-BT: Direct Drive Servo Motor & Automatic Undertrimming & Automatic Backtacking. (The other special features are as CS-820).
- F: Automatic presser foot lifting. (Optional). (AF: Pneumatic type, MF: Electric type.).