



CSR-8891D-LBFT

Direct Drive, Single Needle, Needle Feed & Top / Bottom Roller Feed, Postbed Sewing Machine (With automatic undertrimming & backtacking & roller presser lifting) (Large hook) (Backtacking with power driven roller presser).

Model No. CSR-8891D-LBFT	S.P.M. 2,500
Max.Stitch Length 5mm	Lift Of RollerPresser (Knee) 10mm
Needle System DP×5#16 (#14~#19)	Needle Bar Stroke 42mm

Equipped with direct drive Servo motor to drive the main-shaft directly, reduced friction loss and improve the energy efficiency.
Equipped with backtacking with power driven roller presser, reverse stitch is stitch in stitch "no mismatch".
The new design of low noise backtacking devise can improve the efficiency of sewing.
Applied with 1.6 times capacity large hook, it could reduce the frequency of replacing the bobbin and improve the sewing efficiency.

- Applied with thread trimmer for short thread end, the moveable knife, fix cutter and clamping thread spring all are adjustable.
- Extended needle bar stroke, it could be adapted to various specification of thread (#80/3~#15/3 nylon thread).
- The hand wheel at the level of the middle shaft, operators can turn it easily.
- Equipped magnet sticking type LED lamp, operators can easily adjust the lighting position.
- Machine head equipped with multifunctional button 1.Backtacking 2. Correction stitch (half stitch operation) 3. Safty switch.
- For sewing functional and ornamental seams preferably on concave portions of shoe uppers ,leather products,cylinder workpiece,.....ect..

CS R - 889 1 D - L B F T

Code Description :

R: Backtacking With Power Driven Roller Presser
: Backtacking With Non-Power Driven Roller Presser

Code Description :

D: With Direct Drive Servo Motor
T: Edge Trimming/Lining Trimming (Vertical Type)
K: Edge Trimming/Lining Trimming (Horizontal Type)

Code Description :

: Standard Hook
L: Large Hook

Code Description :

B: Automatic Backtacking
F: Automatic Roller Presser Lifting
T: Automatic Undertrimming
FT: Automatic Undertrimming & Automatic Roller Presser Lifting
BT: Automatic Undertrimming & Automatic Backtacking
BFT: Automatic Undertrimming & Automatic Backtacking & Automatic Roller Presser Lifting

SPECIFICATIONS:

Model No.	Max.Speed S. P. M.	Lifting Of Roller mm	Stitch Length mm	Needle System	Automatic Backtacking	Automatic Trimming	Edge Trimming & Lining Trimming
CSR-8891D-BFT	2500	10	5.0	DP×5	○	○	
CS-8891D-BFT	2500	10	5.0		○	○	
CSR-8891D-BT	2500	10	5.0		○	○	
CS-8891D-BT	2500	10	5.0	DP×5	○	○	
CSR-8891DT-LBFT	2500	10	5.0		○	○	○ (Vertical Type)
CS-8891DT-LBFT	2500	10	5.0		○	○	○ (Vertical Type)
CSR-8891D-B	2500	10	5.0	DP×5	○		
CS-8891D-B	2500	10	5.0		○		
CSR-8891D-LBFT	2500	10	5.0		○	○	
CS-8891D-LBFT	2500	10	5.0	DP×5	○	○	
CSR-8891D-LBT	2500	10	5.0		○	○	
CS-8891D-LBT	2500	10	5.0		○	○	
CSR-8891D-LT	2500	10	5.0	DP×5		○	
CS-8891D-LT	2500	10	5.0			○	
CSR-8891D-LB	2500	10	5.0		○		
CS-8891D-LB	2500	10	5.0	DP×5	○		
CSR-8891DK-LBFT	2500	10	5.0		○	○	○ (Horizontal Type)
CS-8891DK-LBFT	2500	10	5.0		○	○	○ (Horizontal Type)

CSR-8891D-LBFT



- CSR-8891D-HBFT
Suitable for thick thread and heavy material stitching. Needle system DPx17, The other special features are as CSA-8891D-BFT.

CSRS-8891AD-BFT



Overseas patents obtained.
Any imitation copies will be accused.

- CSRS-8891D-LBFT
Applied with new design thread end trimming mechanism of upper thread, the length of upper thread end is less than 2mm, no need second time to cut thread end, effectively improve the production efficiency. The other special features are as CSR-8891D-LBFT.
- CSRS-8891AD-BFT
Direct Drive, Integrated type. (The other features are as same as above machines.)