

電熱蒸汽發生器

ELECTRIC STEAM GENERATOR

優點：

- 產品採用電能作為能源，利用先進的生產工藝和成熟的技術打造。結構緊湊，熱效率≥99%、運行無噪音、100%
- 無污染、無公害的綠色環保產品，結構簡單、易于保養。
- 全自動控制、操作方便，採用優質電熱組件、使用壽命長，
- 加熱實現分組控制，節省電耗。
- 產品具備壓力、溫度、水位等多重聯鎖安全保護控制，電子水位控制裝置可通過蜂鳴器與顯示器，以警示最低水位，確保安全操作。
- 產品採用手動/自動兩種給水水箱方式，無自來水接入時，可人工作業，配置使水泵進水始終處於高位，不易進空氣；
- 產品採用特有的尾汽再回收利用技術，使鍋爐進水溫度達到50°C以上，實現零排放并大幅節省電費。
- 大容量不銹鋼給水箱，耐腐蝕不生鏽，使用壽命長。
- 產品配置了多組出汽分接口和回水分接口，滿足了不同場合的用汽和回水需求。



OPB-9KW~36KW

免
報
裝

Feature:

- Electric type boiler, with advanced technology, 99% heating efficiency, simply and easy to maintain, eco-environment products.
- Auto controlling, friendly operation, adopted with high quality heating element for long-time usage, energy saving.
- Multi-safety protection control of pressure, temperature and water level, when the water is in low level, the panel will show the message E3 and also buzzer alarm for reminding.
- Auto or manual water supply, water tank in the top which the water pump may not get air in.
- With special steam recycle technology, it can makes the inflow water reach to 50°C above. No water drain out and power saving.
- Big volume of steel stainless of water supply tank, it is durable and won't get rusty.
- Settle with multi-function of atmolytic and backwater interface to satisfy different demand.



OPB-48KW~108KW

鍋爐型號 Model		全自動電蒸氣鍋爐								
		OPB-9K	OPB-12K	OPB-18K	OPB-24K	OPB-36K	OPB-48K	OPB-72K	OPB-108K	
性 能 Specifi cation	額定蒸發量 Rated evaporation	kg/h	12	16	24	32	50	64	100	150
	電功率 Volume	kW	9	12	18	24	36	48	72	108
	發熱管數量 Number of heating tubes	pc/kW	1*9	1*12	1*18	2*12	2*18	4*12	4*18	6*18
	額定蒸汽壓力 Rated steam pressure	Mpa	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7
	額定蒸汽溫度 Rated steam temperature	°C	170	170	170	170	170	170	170	170
	水容積 Water volume	L	30	30	30	30	30	30	30	30
	設計熱效率 Design efficiency	%	≥99			≥99				
連接 管口 Connector outlet	給水閥 Feedwater valve	mm	G1/2"			G1/2"				
	蒸汽出口 Steam outlet	mm	G1/2"			G1/2"	G3/4"			
	排污口 The sewage outfall	mm	G3/4"			G3/4"	G3/4"			
	安全閥放口 Safety valve caliber	mm	G1/2"			G1/2"	G3/4"			
規 格 Dimension	鍋爐重量 Equipment weight	kg	60		75	75	115			150
	長 Length	mm	690		730	730	750			820
	寬 Width	mm	410		450	450	620			620
	高 Height	mm	960		1180	1180	1180			1280