

CYLINDER-BED/UNISON FEED

GOLDEN WHEEL



CS-8243

Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Large hook).

Model No. CS-8243	S.P.M. 2,000
Max. Stitch Length 6mm	Lift Of Presser Foot (Knee) 13mm
Needle System DP×17 #23 (#20~#25)	Needle Bar Stroke 36mm
Alternating Movement 3~7mm	

Equipped with a safety clutch mechanism which protected the rotating hook & needle from damage when the thread was caught in the rotating hook.

The diameter of cylinder-bed is 72 mm, is ideally suited for stitching tubular and curved articles, such as shoes, bags, small articles, purses, luggages, .....etc..

- Applied with large hook ensured high sewing efficiency.
- This machine is equipped with walking foot, needle feed and feed dog, all of which act completely in unison feed. Consequently, the upper or lower sewing material did not slip and also this machine can sew accurately and easily several sheets of heavy materials piled up together.
- The stitch length adjusting dial can be turned with ease, and with light touch to the lever, stitching can be reversed.

CS-824

2

Model:

Unison Feed, Cylinder-Bed Sewing Machine.

Code Description:

- 2: Single Needle, Standard Hook. (The diameter of cylinder-bed is 72mm)
- 3: Single Needle, Large Hook. (The diameter of cylinder-bed is 72mm)
- 4: Double Needle, Standard Hook. (The diameter of cylinder-bed is 81mm)
- 4L: Double Needle, Large Hook. (The diameter of cylinder-bed is 81mm)
- 5: Single Needle, Standard Hook. (Elliptical movement of bottom feed, for normal stitching)(The diameter of cylinder-bed is 65mm)
- 5V: Single Needle, Standard Hook. (Horizontal movement of bottom feed, for binding stitching)(The diameter of cylinder-bed is 65mm)

SPECIFICATIONS:

Model No.	Max. Sewing Speed S.P.M.	Lifting Of Presser Foot (Knee) mm	Max. Stitch Length mm	Needle Bar Stroke mm	Hook System	Needle System	The Alternating Movement Of Presser Foot mm
CS-8242	2000	13	6	36	Standard Hook	DP×17#23 (#20~#25)	3~7
CS-8243	2000	13	6	36	Large Hook	DP×17#23 (#20~#25)	3~7
CS-8244	2000	13	6	36	Standard Hook	DP×17#23 (#20~#25)	3~7
CS-8244L	2000	13	6	36	Large Hook	DP×17#23 (#20~#25)	3~7
CS-8245	2000	13	5	36	Standard Hook	DP×17#23 (#20~#25)	3~7
CS-8245V	2000	13	5	36	Standard Hook	DP×17#23 (#20~#25)	3~7

CS-8244L



Double Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Large hook).

- Applied with large hook, increase the sewing efficiency, and get a perfect seam.
- Standard needle gauge: 6.4mm .

CS-8242



Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Standard hook).

CS-8244L1-K



Single Needle, Unison-feed Lock-stitch Machine With Edge Cutter (On-off Side Cutter)(With Automatic Presser Foot)

- Using side edge cutter mechanism, the machine can simultaneously stitching and cutting on various medium heavy material, save time and labor.
- The distance between the needle and the edge cutter can be changed by the simple change of the sub-gauges.
- The upper and lower cutter switch attachment can conveniently control the cutter and automatical presser foot lift.

GOLDEN WHEEL