



### CS-8703

Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Standard hook) (Elliptical movement of bottom feed, for normal stitching).

Model No. <b>CS-8703</b>	S.P.M. <b>2,000</b>
Max. Stitch Length <b>7mm</b>	Lift Of Presser Foot (Knee) <b>15mm</b>
Needle System <b>DP×17 #21 (#18-#22)</b>	Needle Bar Stroke <b>38mm</b>
Alternating Movement <b>2-6mm</b>	
Dia. Of Cylinder-Bed <b>47mm</b>	

With unison feed ensured good feeding characteristics, even on materials with rough, slippery or tacky surfaces, accurate and uniform stitches to be obtained.

- Applied the new type of stitch length adjusting mechanism, precisely stitch length setting & stitch length of forward-stitching and backtacking could be easily adjusted.
- With light touch to the lever, stitching can be reversed.
- Applied with the new type of "double supporting-point backtacking mechanism", durable & ensured the precise backtacking seams.
- Ideally suited for normal stitching tubular and curved articles, such as shoes, bags, small articles, purses,.....etc..

CS-8703

V

-

BT

Model:

**CS-8703:**

Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Standard hook)

**CS-8713:**

Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Large hook)

Code Description:

**:** Elliptical Movement Of Bottom Feed. (For normal stitching)

**V:** Horizontal Movement Of Bottom Feed. (For binding stitching)

**D:** With Direct Drive Servo Motor

Code Description:

**BT:** Automatic Undertrimming & Automatic Backtacking

**AF:** Automatic Presser Foot Lifting (Pneumatic Type)

**MF:** Automatic Presser Foot Lifting (Electric Type)

### SPECIFICATIONS:

Model No.	Max. Sewing Speed S.P.M.	Lifting Of Presser Foot (Knee) mm	Max. Stitch Length mm	Needle Bar Stroke mm	Needle System	The Alternating Movement Of Presser Foot mm	Cylinder Diameter mm	Hook System
CS-8703	2000	15	7	38	DP×17 #21 (#18-#22)	2-6	47	Standard Hook
CS-8703V	2000	15	7	38				Large Hook
CS-8713	2000	15	7	38				Standard Hook
CS-8713V	2000	15	7	38				Large Hook
CS-8703BT	2000	15	7	38	DP×17 #21 (#18-#22)	2-6	47	Standard Hook
CS-8713BT	2000	15	7	38				Large Hook
CS-8703V-BT	2000	15	7	38				Standard Hook
CS-8713V-BT	2000	15	7	38				Large Hook
CS-8703D-BT	2000	15	7	38	DP×17 #21 (#18-#22)	2-6	47	Standard Hook
CS-8713D-BT	2000	15	7	38				Large Hook

### CS-8703V



Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Horizontal movement of bottom feed, for binding stitching) (Standard hook, for medium materials-heavy materials)

- Suitable for stitching (taping or piping or binding) the medium and heavy materials. (For example: bags, shoes, purses and other tubular goods).

### CS-8713D-BT



Single Needle, Unison Feed, Cylinder-Bed Sewing Machine. (Elliptical movement of bottom feed, for normal stitching.) (Large hook, for heavy materials) (With Direct Drive Servo Motor) (Automatic Undertrimming & Automatic Backtacking)

- Applied with large hook, could increase the sewing efficiency.